

MOL-PROGUARD OHC

Cable Filling Grease

Description:

MOL- PROGUARD OHC is a special inorganic grease for high temperatures and multipurpose usage. It assures excellent lubricating properties and strong resistance to oxidation. It is made with a high viscosity base oil, suitable where water resistance property and adhesion to the metal surfaces are required.

Features:

- Easily pumpable by grease gun or centralized lubrication systems.
- Outstanding resistance to oxidation.
- Optimum lubrication under high temperature.
- Superior mechanical resistance.
- Good rust protection.
- High water wash-out property.
- Economical use due to tacky structure.

Applications:

MOL- PROGUARD OHC is suitable for lubrication with high temperatures up to +180°C. It can be used as cable filling grease as well as for overhead line conductor lubrication.

Health, Safety and Environment:

- Normal safety precautions (gloves and safety goggles) Should be employed
- Avoid eye and prolonged skin contact.
- Wash thoroughly after handling material.
- Don't discharge used oil in drains, dispose to an authorized used oil collection point
- For more information, please see the Material Safety Data Sheet (MSDS).

Storage Conditions:

- Should be stored sealed under normal conditions.
- Shelf life in original package and at room temperature is 2 years

Packing Available in:

- 16 KG - 180 KG

Physical and Chemical Conditions:

MOL- PROGUARD OHC	Value
Appearance	Brown/Red
Base Fluid	Mineral
Thickener	Inorganic Bentonite
NLGI	2
Worked Penetration 60 db. strokes, (1/10 mm)	265-295
Dropping Point	Non melt