

MOL-RUSTSTOP 50 W

Product Description:

MOL-RUSTSTOP 50 W is a water soluble rust preventive based on mineral oil, preventive and emulsifiers additives. It forms an opaque white, stable and homogenous emulsion once mixed with water. It forms a thin oily non-sticky film on the bare or phosphate metal surfaces, which provides excellent corrosion protection.

Properties:

- Can be safely used in conditions where rust is a concern especially on the iron and steel materials.
- Provides effective protection against corrosion
- Cleaned easily from the metal surface in solvent or alkaline degreasing baths.

Applications:

- Prepared as an emulsion by mixing with water at 70°C with concentrations between 5-20% depending on the desired film thickness.
- application surface should be clean and dry.
- used as an anti-corrosive fluid inside the radiator and hydraulic water systems..

Health, Safety and Environment:

- Normal safety precautions (gloves and safety goggles) Should be employed
- Avoid eye and prolonged skin contact.
- Wash thoroughly after handling material.
- Don't discharge used oil in drains, dispose to an authorized used oil collection point
- For more information, please see the Material Safety Data Sheet (MSDS).

Storage Conditions:

- Should be stored sealed under normal conditions.
- Shelf life in original package and at room temperature is 2 years

Packing Available in:

- 20 Lit - 208 Lit

Physical and Chemical Conditions:

MOL-RUSTSTOP 50 W	Value
Appearance	Visual Brown, Clear
Density @ 15°C, g/cm ³ ASTM D 1298	0.93
Flash Point (COC), °C ASTM D 92 min	160
Kinematic Viscosity @ 40°C, cSt	58
pH @ 5% DIN 51369	9.5
Refractometer Coefficient	0.95
Corrosion Test @ 5% DIN 51360/2	0-0

*Meets the requirements of the OEM manufacturer.

*The stated values can fluctuate within the normal range.