

MOL-ATF III

Heavy Duty Automotive Gear Lubricants

Product description:

MOL-ATF III is a medium viscosity GM Dexron III red colored automatic transmission fluid especially designed for torque converters and transmissions.

Features :

- ❖ Optimum viscosity providing extra fuel efficiency.
- ❖ Provides consistent shift performance for the life of the vehicle.
- ❖ Extends transmission life and prevents fluid breakdown at higher operating temperatures.
- ❖ Protects transmission gears and allows them to operate smoothly.
- ❖ Maintains lubricity.
- ❖ Flows well for cold start-up.

Meets the specification:

GM Dexron III

Typical properties:

Mol- ATF III	Test Method	III
Appearance	Visual	Red
Density @ 15°C,g/cm ³	ASTM D 4052	0.8804
Kinematic Viscosity @ 40°C.cSt	ASTM D 445	37.05
Kinematic Viscosity @ 100°C.cSt	ASTM D 445	6.127
Viscosity index	ASTM D 2270	122
Pour Point , °C	ASTM D 6749	-34

Packaging and Storage Conditions:

Should be stored sealed under normal storage conditions. Shelf life in original package and at room temperature is 5 years. Available in 1 LT & 3 LT plastic pails and 208 LT drums.

Human Health and Work Safety:

Normal safety precautions (i.e. gloves and safety goggles) should be employed when handling. Avoid eye and prolonged skin contact. Wash thoroughly after handling material. For more information please see the Material Safety Data Sheet (MSDS).

MOLLUBE

Reino Unido, Londres ,71 Shelton St, WC2H 9BP

Tel: +447384440009

info@mollube.co.uk

www.Mollube.co.uk
