

PLATINIUM SUPER SERIES

Product Description:

MOLLUBE PLATINIUM SUPER SERIES is engine oil formulated from specially refined paraffinic base oil with the most modern friction modifier detergent-dispersant, anti corrosion anti wear and other protective properties.

Features:

- Control forming of deposit and sludge, so keeps engine parts clean.
- Maintain its lubrication even under extreme operating conditions.
- Maintain its protection until the next oil change.
- Protect the engine against corrosion and wear due to special additives.

Applications:

MOLLUBE PLATINIUM SUPER SERIES is suitable to use in 4-strook natural aspirated gasoline engine, turbocharged and supercharged engines of passenger vehicles, light commercial vehicles and ideal for high mileage vehicles

Specifications:

- API SL/CF
- ACEA A2/B2

Health, Safety and Environment:

- Normal safety precautions (gloves and safety goggles) Should be employed
- Avoid eye and prolonged skin contact.
- Wash thoroughly after handling material.
- Don't discharge used oil in drains, dispose to an authorized used oil collection point
- For more information, please see the Material Safety Data Sheet (MSDS).

Storage Conditions:

- Should be stored sealed under normal conditions.
- Shelf life in original package and at room temperature is 3 years

Packing Available in:

- 1 lit - 20 lit
- 5 lit - 208 lit

Physical and Chemical Conditions:

MOLLUBE PLATINIUM SUPER	Method	Unit	15W-40	20W-50
Density @ 15° C	ASTM D 4052	g/cm ³	0.885	0.89
Kinematic Viscosity @ 40° C	ASTM D 445	cSt	148	179.8
Kinematic Viscosity @ 100° C	ASTM D 445	cSt	13.5	20
Viscosity Index	ASTM D 2270	-	150	150
Flash Point, (COC)	ASTM D 92	°C	255	255
Pour Point	ASTM D 97	°C	-25	-23

*Meets the requirements of the OEM manufacturer.

*The stated values can fluctuate within the normal range.